



- ECO
- HP
- UHP
- SUV/4X4
- Light Truck & Van
- Special Service

**HANMIX INTERNATIONAL  
COMPANY LIMITED**

Add: Room 604, Building 1,  
Celebrity International, No.39  
Shiling Road Laoshan District,  
Qingdao, China

E-mail: [Info@hanmix.net](mailto:Info@hanmix.net)

**WWW.HANMIX.NET**

 **PCR**



  
**tires**



Tel: +86 532 8086 7001  
+86 532 6888 7003  
Fax: +86 532 8086 7001

**WWW.HANMIX.NET**

# INFORMATION

Welcome to the Hanmix World. Hanmix is not only a brand name, but a way for a better life. You can find security, safety and high quality life in the Hanmix World.

Hanmix covers over 600 kinds of products, including Bicycle tires, PCR tires, OTR tires, Industrial Tires, Agricultural tires, TBR tires, TBB tires, LTB tires, Solid tires, Inner tubes, Flaps, Batteries and Valves.

Our product certified by DOT, ECE, CCC, GCC, can satisfy the customers' demands to the great extent. All of our products comply with international quality standards and are greatly appreciated in a variety of different markets throughout the world. Hanmix is a global brand name, which is providing better solutions for your demands.

# CONTENTS

## ECONOMIC (ECO)

Summer.....	p3-6
Winter.....	p25

## HIGH PERFORMANCE (HP)

Summer.....	p7
Winter.....	p25

## ULTRA HIGH PERFORMANCE (UHP)

Summer.....	p11-14
All Season.....	p9

## SPORT UTILITY VEHICLE (SUV/4X4)

Winter.....	p25
All Season.....	p15-24

## LIGHT TRUCK& VAN

Winter.....	p25
All Season.....	p27-30

## SPECIAL SERVICE

All Season.....	p31-34
-----------------	--------





# MIX-PCR H



Balanced performance: Silence, Fuel Efficiency,  
Security, Comfort.

All season design.

Variable pith and noise  
reducing shoulder deliver  
silent journey.

- Silica compound provides excellent fuel efficiency.
- Special tread outline and section design improve handling stability and comfort.



# MIX-PCR



Design of overall and longitudinal continuous pattern

Reasonable rigidity distribution on tyre treads

45° groove design

The design of three-dimensional sheet steel on tyre shoulder

Design of four wide longitudinal furrows with relatively large amount of grooves



# HANMIX

page37

## MIX-FORTY



● Balanced performance:

Stability,  
Silence,  
Security,  
Mileage.

● Asymmetrical tread

design provides  
excellent grip  
and handling.

● Silica compound  
delivers reduced  
rolling resistance  
for better fuel  
efficiency.

● Strong block tread  
design improves  
mileage, stability  
and security.



The asymmetrical design provides excellent grip in both dry and wet conditions, enhances turning handling.



Variable pith on both sides reduces noise.



Strong circumferential central rib improves straight line stability.



The corrugated central grooves direct water, the wide-angle grooves enhance anti-hydroplaning capabilities. It runs easily on downpour highway.



Rim protector designed.

The updated SSBR and silica compound provide excellent wet grip, much reduced rolling resistance, and terrific handling in high speed.



**HANMIX**

page38

**MIX-MORA AS**

# MIX-MORA SR



Revolutionary tread design, rising strength from inside to outside, can deal with both smooth mountain road and downpour highway, at leisure.

The updated SSBR and silica compound provide excellent wet grip, much reduced rolling resistance, and terrific handling in high speed.

Special asymmetrical design provides excellent grip and handling in both dry and wet conditions.

The dramatic 2 central big grooves with special compound, enhances efficient water evacuation to deal with all conditions.

Sipes on outside shoulder enhance turning handling and low down noise in high speed.



# MIX-MORA



Outside big  
pattern blocks.



Four wide vertical  
main ditches.



Innovative silica  
formula in the  
tread.



Design of noise  
reducing openings  
on shoulder.

# MIX-HAWI

• Four wide circumferential grooves with lugs provide effective water drainage, improve security in wet conditions.

• Crooked sipes reduce water film a lot and prevent hydroplaning.

Solid uniform tread blocks with circumferential ribs improve straight line stability.

• Step grooves floor prevents pebbles.

3D steps on shoulder, provides attractive appearance and improves heat dissipation.





**HANMIX**

page41

**MIX-HARD**

# HANMIX page41

## MIX-MUD



Big pattern blocks and wider grips, provide excellent driving force, grips and anti-skidding on off roads.



Protecting dam and rough design on shoulder improve impact resistance and durability.



Hexagon bead ring with single endless steel wire improves a lot the stability.



Double or triple casings improve strength a lot, meet the demand of the worst condition.



# MIX-THIRTY



Tapered grooves enhance blocks stability, steady shoulder improves

grips.

The wide grooves with special compound, enhance efficient water evacuation to deal with all conditions



Semi-closed tread grooves outside the tread, provides silence.

Asymmetrical design brings excellent grips, breaking, and better handling.

# HANMIX page42

## MIX-COR



● Crisscross pattern groove design.



● Ladder tyre of decorative pattern design.



● The design of central continuous fillet.



● The design of strong tread shoulder.



● Four ribs and continuous grips getting wider from centre to shoulder, provide excellent snow removals.



● Special cold resistance compound for tread provide excellent breaking and safety.



Improved shoulder blocks and small absorption holes, provide excellent grips on wet, snow and ice road.



● Detailed 3D sipes improve grips and traction on snow road, also improve the strength of blocks, providing excellent handling.



# MIX-ICE



page43

● Circumferential tread blocks on shoulders deliver excellent stability and handling.



● Two circumferential central ribs provide super wear-resistance.



● Special outline avoid eccentric wear.



● Convex tread blocks provide excellent traction and prevent sideslip.



**HANMIX** page44

**MIX-PIC BR**





● Continuous zigzag and longitudinal draining furrows.



● The design of wear-resistance tyre shoulder.



● The design of exquisite siping pattern.



● The design of central continuous fillet.



**MIX-PIC**

**HANMIX**

page44

# MIX-PIC TAXI

• Two circumferential central ribs provide super wear-resistance.



• Imported hyperfine carbon improves a lot mileage and reduces rolling resistance much.



• Circumferential tread blocks on shoulders deliver excellent stability, handling and security.



● Special outline and compound provides overlong mileage.



● Four wide grooves deliver excellent water evacuation.



Endless steel beading and belts provide uniformity and comfort.



● Symmetrical design delivers low noise.



● All Season design.



**H HANMIX**

**MIX-TOUR**

page45

# MIX-PCR H

UTQG: 440/AA/A



comfort  
silence  
fuel-saving  
safety

INCH	SIZE	TYPE	STD/X L	LOAD INDEX / SPEED SYMBOL	STD RIM	MAX. LOAD	MAX. PRESSU RE	TIRE DIMENSION		EU LABEL DATA			
					INCH	KG	KPA	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)				
13	165/65R13	Economic		77	5.0	412	300	544	170	E	C	2	70
	155/70R13	Economic		75	4.5	387	300	548	157	E	C	2	70
	165/70R13	Economic		79	5.0	437	300	562	170	E	C	2	70
	165/70R13	Economic	XL	83	5.0	487	340	562	170	E	C	2	70
	175/70R13	Economic		82	5.0	475	300	576	177	E	C	2	70
	185/70R13	Economic		86	5.5	530	300	590	189	E	C	2	70
14	195/60R14	Economic		86	6.0	530	300	590	201	E	C	2	71
	155/65R14	Economic		75	4.5	387	300	558	157	E	C	2	70
	175/65R14	Economic		82	5.0	475	300	584	177	E	C	2	70
	175/65R14	Economic	XL	86	5.0	530	340	584	177	E	C	2	70
	185/65R14	Economic		86	5.5	530	300	596	189	E	C	2	70
	165/70R14	Economic		81	5.0	462	300	588	170	E	C	2	70
15	175/70R14	Economic		84	5.0	500	300	602	177	E	C	2	70
	195/55R15	Economic		85	6.0	515	300	595	201	E	C	2	71
	195/60R15	Economic		88	6.0	560	300	615	201	E	C	2	71
	205/60R15	Economic		91	6.0	615	300	627	209	E	C	2	71
	215/60R15	Economic		94	6.5	670	300	639	221	E	C	2	71
	185/65R15	Economic		88	5.5	560	300	621	189	E	C	2	70
	185/65R15	Economic	XL	92	5.5	560	340	621	189	E	C	2	70
	195/65R15	Economic		91	6.0	615	300	635	201	E	C	2	71
	195/65R15	Economic	XL	95	6.0	690	340	635	201	E	C	2	71
	205/65R15	Economic		94	6.0	670	300	647	209	E	C	2	71
16	215/65R15	Economic		96	6.5	710	300	661	221	C	C	2	71
	215/65R15	Economic	XL	100	6.5	800	340	661	221	C	C	2	71
	205/55R16	Economic		91	6.5	615	300	632	214	E	C	2	71
	205/60R16	Economic		92	6.0	630	300	652	209	E	C	2	71
	205/60R16	Economic	XL	96	6.0	710	340	652	209	C	C	2	71
	215/60R16	Economic		95	6.5	690	300	664	221	E	C	2	71
	215/60R16	Economic	XL	99	6.5	775	340	664	221	C	C	2	71
	225/60R16	Economic		98	6.5	750	300	676	228	C	C	2	71
	235/60R16	Economic		100	7.0	800	300	688	240	C	C	2	71
	205/65R16	Economic		95	6.0	690	300	672	209	E	C	2	71
17	215/65R16	Economic		98	6.5	750	300	686	221	C	C	2	71
	225/70R16	Economic		103	6.5	875	300	722	228	C	C	2	71
	215/60R17	Economic		96	6.5	710	300	690	221	C	C	2	71
	225/65R17	Economic		102	6.5	850	300	724	228	C	C	2	71
	235/55R17	Economic		104	7.0	900	300	738	240	C	C	2	71
	225/60R18	Economic		100	6.5	800	300	727	228	C	C	2	71

# MIX-PCR



comfort  
silence  
fuel-saving  
safety

INCH	SIZE	TYPE	LOAD INDEX / SPEED SYMBOL	APPROVED RIM	MAX. LOAD	MAX. PRESSU RE	TIRE DIMENSION	
				INCH	KG	KPA	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)
13	155/70R13	Economic	75T	4.0-4.5-5.0	387	250	548	157
	165/70R13	Economic	79T	4.0-5.0-5.5	437	250	562	170
	165/70R13	Economic	79H	4.0-5.0-5.5	437	250	562	170
	175/70R13	Economic	82T	4.5-5.0-6.0	475	250	576	177
	175/70R13	Economic	82H	4.5-5.0-6.0	475	250	576	177
	155/80R13	Economic	79T	4.0-4.5-5.0	437	250	578	157
	185/60R14	Economic	82T	5.0-5.5-6.5	475	250	578	189
	185/60R14	Economic	82H	5.0-5.5-6.5	475	250	578	189
14	195/60R14	Economic	86T	5.5-6.0-7.0	530	250	590	201
	195/60R14	Economic	86H	5.5-6.0-7.0	530	250	590	201
	175/65R14	Economic	82T	5.0-5.5-6.0	475	250	584	177
	175/65R14	Economic	82H	5.0-5.5-6.0	475	250	584	177
	185/65R14	Economic	86T	5.0-5.5-6.5	530	250	596	189
	185/65R14	Economic	86H	5.0-5.5-6.5	530	250	596	189
	185/70R14	Economic	88T	4.5-5.5-6.0	560	250	616	189
	185/70R14	Economic	88H	4.5-5.5-6.0	560	250	616	189
	195/70R14	Economic	95T	5.0-6.0-6.5	690	290	630	201
	195/70R14	Economic	95H	5.0-6.0-6.5	690	290	630	201
15	205/70R14	Economic	98T	5.0-6.0-7.0	750	290	644	209
	205/70R14	Economic	98H	5.0-6.0-7.0	750	290	644	209
	195/60R15	Economic	88H	5.5-6.0-7.0	560	250	615	201
	195/60R15	Economic	88V	5.5-6.0-7.0	560	250	615	201
	205/60R15	Economic	91T	5.5-6.0-7.5	615	250	627	209
	205/60R15	Economic	91H	5.5-6.0-7.5	615	250	627	209
	215/60R15	Economic	94T	6.0-6.5-7.0	670	250	639	221
	215/60R15	Economic	94H	6.0-6.5-7.0	670	250	639	221
	185/65R15	Economic	88T	5.0-5.5-6.5	560	250	621	189
	185/65R15	Economic	88H	5.0-5.5-6.5	560	250	621	189
15	195/65R15	Economic	91H	5.5-6.0-7.0	615	250	635	201
	195/65R15	Economic	91V	5.5-6.0-7.0	615	250	635	201
	205/65R15	Economic	94H	5.5-6.0-7.5	670	250	647	209
	205/65R15	Economic	94V	5.5-6.0-7.5	670	250	647	209
	205/65R15	Economic	94V	5.5-6.0-7.5	670	250	647	209

# MIX-PCR

INCH	SIZE	TYPE	LOAD INDEX / SPEED SYMBOL	APPROVED RIM	MAX. LOAD	MAX. PRESSURE	TIRE DIMENSION		EU LABEL DATA			
				INCH	KG	KPA	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)				
15	215/70R15	Economic	98T	5.5-6.5-7.0	750	250	683	221				
	215/70R15	Economic	98H	5.5-6.5-7.0	750	250	683	221				
	205/70R15	Economic	96T	5.0-6.0-7.0	710	250	669	209				
	205/70R15	Economic	96H	5.0-6.0-7.0	710	250	669	209				
	205/55R16	Economic	94V	5.5-6.5-7.5	670	290	632	214				
16	205/55R16	Economic	94W	5.5-6.5-7.5	670	290	632	214				
	215/55R16	Economic	97V	6.0-7.0-7.5	730	290	642	226				
	215/55R16	Economic	97W	6.0-7.0-7.5	730	290	642	226				
	225/55R16	Economic	99V	6.0-7.0-8.0	775	290	654	233				
	225/55R16	Economic	99W	6.0-7.0-8.0	775	290	654	233				
	215/60R16	Economic	95H	6.0-6.5-7.5	690	250	664	221				
	215/60R16	Economic	95V	6.0-6.5-7.5	690	250	664	221				
	225/60R16	Economic	98H	6.0-6.5-8.0	750	250	676	228				
	225/60R16	Economic	98V	6.0-6.5-8.0	750	250	676	228				

# MIX-FORTY

UTQG: 420/A/A



INCH	SIZE	TYPE	STD/X L	LOAD INDEX / SPEED SYMBOL	STD RIM	MAX. LOAD	MAX. PRESSURE	TIRE DIMENSION		EU LABEL DATA			
					INCH	KG	KPA	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)				
14	185/60R14	High performance		82	5.5	475	300	578	189	E	C	2	70
	185/65R14	High performance		86	5.5	530	300	586	189	E	C	2	70
	185/70R14	High performance		88	5.5	560	300	616	189	E	C	2	70
	195/70R14	High performance		91	6.0	615	300	630	201	C	C	2	71
	195/70R14	High performance	XL	95	6.0	690	340	630	201	C	C	2	71
15	195/50R15	High performance		82	6.0	475	300	577	201	E	C	2	71
	185/55R15	High performance		82	6.0	475	300	585	194	E	C	2	70
	195/55R15	High performance		85	6.0	515	300	595	201	E	C	2	71
	185/60R15	High performance		84	5.5	500	300	603	189	E	C	2	70
	185/60R15	High performance	XL	88	5.5	560	340	603	189	E	C	2	70

# MIX-FORTY

INCH	SIZE	TYPE	STD/X L	LOAD INDEX / SPEED SYMBOL	STD RIM	MAX. LOAD	MAX. PRESSURE	TIRE DIMENSION		EU LABEL DATA			
					INCH	KG	KPA	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)				
15	195/60R15	High performance		88	6.0	560	300	615	201	E	C	2	71
	185/65R15	High performance		88	5.5	560	300	621	189	E	C	2	70
	185/65R15	High performance	XL	92	5.5	630	340	621	189	C	C	2	70
	195/65R15	High performance		91	6.0	615	300	635	201	C	C	2	71
	195/65R15	High performance	XL	95	6.0	690	340	635	201	C	C	2	71
	205/65R15	High performance		94	6.0	670	300	647	209	C	C	2	71
	215/65R15	High performance		96	6.5	710	300	661	221	C	C	2	71
	215/65R15	High performance	XL	100	6.5	800	340	661	221	C	C	2	71
	205/50R16	High performance		87	6.5	545	300	612	214	E	C	2	71
	205/55R16	High performance		91	6.5	615	300	632	214	C	C	2	71
	16	225/55R16	High performance		95	7.0	690	300	654	233	C	C	2
205/60R16		High performance		92	6.0	630	300	652	209	C	C	2	71
205/60R16		High performance	XL	96	6.0	710	340	652	209	C	C	2	71
215/60R16		High performance		95	6.5	690	300	664	221	C	C	2	71
215/60R16		High performance	XL	99	6.5	775	340	664	221	C	C	2	71
225/60R16		High performance		98	6.5	750	300	676	228	C	C	2	71
215/65R16		High performance		98	6.5	750	300	686	221	C	C	2	71
225/60R17		High performance		99	6.5	775	300	702	228	C	C	2	71
225/65R17		High performance		102	6.5	850	300	724	228	C	C	2	71

# MIX-MORA 25

UTQG: 420/AA/A



INCH	SIZE	TYPE	STD/X L	LOAD INDEX / SPEED SYMBOL	STD RIM	MAX. LOAD	MAX. PRESSURE	TIRE DIMENSION		EU LABEL DATA			
					INCH	KG	KPA	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)				
16	205/50Zr16	UHP		87	6.5	545	300	612	214	C	B	2	71
	205/55Zr16	UHP		91	6.5	615	300	632	214	C	B	2	71
	215/55Zr16	UHP		93	7.0	650	300	642	226	C	B	2	71
	225/55Zr16	UHP		95	7.0	690	300	654	233	C	B	2	71
17	205/45Zr17	UHP	XL	88	7.0	560	340	616	206	C	B	2	71
	215/45Zr17	UHP	XL	91	7.0	615	340	626	213	C	B	2	71
	225/45Zr17	UHP	XL	94	7.5	670	340	634	225	C	B	2	71
	235/45Zr17	UHP	XL	97	8.0	730	340	644	236	C	B	2	71
18	245/45Zr17	UHP	XL	99	8.0	775	340	652	243	C	B	2	71
	225/40Zr18	UHP	XL	92	8.0	630	340	637	230	C	B	2	71
	235/40Zr18	UHP	XL	95	8.5	690	340	645	241	C	B	2	71
	245/40Zr18	UHP	XL	97	8.5	730	340	653	248	C	B	2	71

# MIX-MORA SR

UTQG: 280/AA/A



INCH	SIZE	TYPE	STD/X L	LOAD INDEX / SPEED SYMBOL	STD RIM	MAX. LOAD	MAX. PRESSURE	TIRE DIMENSION		EU LABEL DATA			
					INCH	KG	KPA	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)				
16	205/50ZR16	UHP	XL	91	6.5	615	340	612	214	C	C	2	71
	225/50ZR16	UHP	XL	96	7.0	710	340	632	233	C	C	2	71
	205/55ZR16	UHP	XL	94	6.5	670	340	632	214	C	C	2	71
	215/55ZR16	UHP	XL	97	7.0	730	340	642	226	C	C	2	71
	225/55ZR16	UHP	XL	99	7.0	775	340	654	233	C	C	2	71
17	205/40ZR17	UHP	XL	84	7.5	500	340	596	212	E	C	2	72
	215/40ZR17	UHP	XL	87	7.5	545	340	604	218	E	C	2	72
	245/40ZR17	UHP	XL	95	8.5	690	340	628	248	C	C	2	72
	205/45ZR17	UHP	XL	88	7.0	560	340	616	206	E	C	2	71
	215/45ZR17	UHP	XL	91	7.0	615	340	626	213	C	C	2	71
18	225/45ZR17	UHP	XL	94	7.5	670	340	634	225	C	C	2	71
	235/45ZR17	UHP	XL	97	8.0	730	340	644	236	C	C	2	72
	245/45ZR17	UHP	XL	99	8.0	775	340	652	243	C	C	2	72
	215/50ZR17	UHP	XL	95	7.0	690	340	648	226	C	C	2	71
	225/50ZR17	UHP	XL	98	7.0	750	340	658	233	C	C	2	71
	235/50ZR17	UHP	XL	100	7.5	800	340	668	245	C	C	2	72
	215/55ZR17	UHP	XL	95	7.0	750	340	668	226	C	C	2	71
	225/55ZR17	UHP	XL	101	7.0	825	340	680	233	C	C	2	71
	235/55ZR17	UHP	XL	103	7.5	875	340	690	245	C	C	2	72
	225/40ZR18	UHP	XL	92	8.0	630	340	637	230	C	C	2	72
19	235/40ZR18	UHP	XL	95	8.5	690	340	645	241	C	C	2	72
	245/40ZR18	UHP	XL	97	8.5	730	340	653	248	C	C	2	72
	215/45ZR18	UHP	XL	93	7.0	650	340	651	213	C	C	2	71
	225/45ZR18	UHP	XL	95	7.5	690	340	659	225	C	C	2	71
	235/45ZR18	UHP	XL	96	8.0	750	340	669	236	C	C	2	72
	245/45ZR18	UHP	XL	100	8.0	800	340	677	243	C	C	2	72
	255/45ZR18	UHP	XL	103	8.5	875	340	687	255	C	C	2	72
20	235/35ZR19	UHP	XL	91	8.5	615	340	647	241	C	C	2	72
	245/35ZR19	UHP	XL	93	8.5	650	340	655	248	C	C	2	72
	225/35ZR20	UHP	XL	90	8.0	600	340	666	230	C	C	2	72
20	235/35ZR20	UHP	XL	92	8.5	630	340	672	241	C	C	2	72
	245/35ZR20	UHP	XL	95	8.5	690	340	680	248	C	C	2	72
	255/35ZR20	UHP	XL	97	9.0	730	340	686	260	C	C	2	72

# MIX-MORA



INCH	SIZE	TYPE	LOAD INDEX / SPEED SYMBOL	APPROVED RIM	MAX. LOAD	MAX. PRESSURE	TIRE DIMENSION	
				INCH	KG	KPA	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)
17	235/45R17	UHP	97W	7.5-8.0-9.0	730	290	644	236
	215/45R17	UHP	91W	7.0-7.5-8.0	615	290	626	213
	225/45R17	UHP	94W	7.0-7.5-8.5	670	290	634	225
	205/50R17	UHP	93W	5.5-6.5-7.5	650	290	638	214
	225/50R17	UHP	94W	6.0-7.0-8.0	670	250	658	233
18	225/40R18	UHP	92W	7.5-8.0-9.0	630	290	637	230
	235/40R18	UHP	95W	8.0-8.5-9.5	690	290	645	241
20	245/35R20	UHP	95W	8.0-8.5-9.5	690	290	680	248

# MIX-HAWI


UTQG: 500/A/A



INCH	SIZE	TYPE	STD/X L	LOAD INDEX / SPEED SYMBOL	STANDARD RIM	MAX. LOAD	MAX. PRESSURE	TIRE DIMENSION		EU LABEL DATA			
					INCH	KG	KPA	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)				
15	235/75R15	SUV		105	6.5	925	300	733	235	C	E	2	72
	235/60R16	SUV		100	7.0	800	300	688	240	E	E	2	72
	215/70R16	SUV		100	6.5	800	300	708	221	E	E	2	72
16	225/70R16	SUV		103	6.5	875	300	722	228	C	E	2	72
	235/70R16	SUV		106	7.0	950	300	736	240	C	E	2	72
	245/70R16	SUV	XL	111	7.0	1090	340	750	248	C	E	2	72
	255/70R16	SUV		111	7.5	1090	300	764	260	C	E	2	72
	265/70R16	SUV		112	8.0	1120	300	778	272	C	E	2	72
	265/75R16	SUV		116	7.5	1250	300	804	267	C	E	2	72
	235/55R17	SUV		99	7.5	775	300	690	245	E	E	2	72
17	225/60R17	SUV		99	6.5	775	300	702	228	E	E	2	72
	225/65R17	SUV		102	6.5	850	300	724	228	C	E	2	72
	235/65R17	SUV	XL	108	7.0	1000	340	738	240	C	E	2	72
	245/65R17	SUV	XL	111	7.0	1090	340	750	248	C	E	2	72
	265/65R17	SUV	XL	116	8.0	1120	300	776	272	C	E	2	72
	265/70R17	SUV		115	8.0	1215	300	804	272	C	E	2	72
18	255/55R18	SUV	XL	108	8.0	1030	340	737	265	C	E	2	72
	235/60R18	SUV	XL	107	7.0	975	340	739	240	C	E	2	72

# MIX-HARD

UTQG: 520/A/B



safety  
drainage  
handling  
off-road

INCH	SIZE	TYPE	STD/X L	LOAD INDEX / SPEED SYMBOL	STANDARD RIM	MAX. LOAD	MAX. PRESSURE	TIRE DIMENSION		EU LABEL DATA							
					INCH			KG	KPA	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)						
18	31x10.5R15LT	SUV	WL	109													
	LT215/75R15	SUV	WL	106W	8.0	880/730	350	703	216								
	LT225/75R15	SUV	WL	10209	8.0	850/775	300	719	223								
	LT235/75R15	SUV	WL	104/101													
19	P215/70R16	SUV	WL	100													
	P245/70R16	SUV	WL	107													
	LT265/70R16	SUV	WL	117/114	8.0	1285/1180	450	778	272								
	LT225/75R16	SUV	WL	110/112													
18	LT245/75R16	SUV	WL	120/116	7.0	1380/1260	350	774	240								
	LT265/75R16	SUV	WL	123/120													
	LT285/75R16	SUV	WL	128/123	8.0	1700/1550	550	834	286								
	LT215/85R16	SUV	WL	115/112													
	LT235/85R16	SUV	WL	120/116	8.5	1380/1260	350	806	235								
17	P265/65R17	SUV	WL	112													
	LT265/70R17	SUV	WL	121/118													

# MIX-MUD



safety  
drainage  
breaking  
off-road

INCH	SIZE	TYPE	STD/X L	LOAD INDEX / SPEED SYMBOL	STANDARD RIM	MAX. LOAD	MAX. PRESSURE	TIRE DIMENSION	
					INCH			KG	KPA
15	31x10.5R15LT	SUV	WL	109					
16	LT245/75R16	SUV	WL	120/116					
	LT265/75R16	SUV	WL	123/120					
	LT285/75R16	SUV	WL	126/123	8.0	1700/1550	550	834	286
	LT235/85R16	SUV	WL	120/116					
17	LT265/70R17	SUV	WL	121/118					

# MIX-THIRTY


UTQG: 300/AA/A



safety  
drainage  
handling  
silence

INCH	SIZE	TYPE	STD/X L	LOAD INDEX / SPEED SYMBOL	STANDARD RIM	MAX. LOAD	MAX. PRESSURE	TIRE DIMENSION		EU LABEL DATA			
					INCH			KG	KPA	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)		
17	235/65R17	SUV	XL	106V	7.0	1000	340	738	240	C	B	2	71
18	255/55R18	SUV	XL	109V	8.0	1030	340	737	265	C	B	2	71
	255/60R18	SUV	XL	112V	7.5	1120	340	763	260	C	B	2	72
19	255/50R19	SUV	XL	107V	8.0	975	340	739	265	C	B	2	72
	255/55R19	SUV	XL	111V	8.0	1090	340	763	265	C	B	2	72
20	275/40R20	SUV	XL	106V	9.5	950	340	728	278	C	B	2	72
	275/45R20	SUV	XL	110V	9.0	1060	340	756	273	C	B	2	72
	265/50R20	SUV	XL	111V	8.5	1090	340	774	277	C	B	2	72
	275/55R20	SUV	XL	117V	8.5	1285	340	810	284	C	B	2	72
	275/60R20	SUV	XL	119V	8.0	1360	340	838	279	C	B	2	72

# MIX-COR



safety  
drainage  
handling  
silence

INCH	SIZE	TYPE	LOAD INDEX / SPEED SYMBOL	APPROVED RIM	MAX. LOAD	MAX. PRESSURE	TIRE DIMENSION	
				INCH			KG	KPA
15	LT235/75R15	SUV	110/107S	6.0-6.5-7.0	2150/975	450	733	235
	255/70R15	SUV	108T	6.5-7.5-8.5	1000	250	739	260
	LT215/75R15	SUV	106/103T	5.5-6.0-7.0	1609/730	350	703	216
16	265/70R16	SUV	112T	7.0-8.0-9.0	1120	250	778	272
	205/80R16	SUV	104T	5.0-5.5-7.0	900	290	734	203
17	225/65R17	SUV	102T	6.0-6.5-8.0	850	250	724	228
	255/65R17	SUV	110T	7.0-7.5-9.0	1060	250	764	260
18	235/60R18	SUV	103T	6.5-7.0-8.5	875	250	739	240
	235/60R18	SUV	103V	6.5-7.0-8.5	875	250	739	240

# MIX-ICE



INCH	SIZE	TYPE	STD./X L	LOAD INDEX / SPEED SYMBOL	APPROVED RIM	MAX. LOAD	MAX. PRESSURE	TIRE DIMENSION		EU LABEL DATA			
					INCH	KG	KPA	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)				
13	155/65R13	WINTER		73 Q/T	4.5	365	300	532	157	C	C	2	69
	165/70R13	WINTER		79 Q/T	5.0	437	300	562	170	C	C	2	69
	175/70R13	WINTER		82 Q/T	5.0	475	300	576	177	C	C	2	69
14	185/60R14	WINTER		82 Q/T	5.5	475	300	578	189	C	C	2	70
	195/60R14	WINTER		86 Q/T	6.0	530	300	590	201	C	C	2	70
	175/65R14	WINTER		82 Q/T	5.0	475	300	584	177	C	C	2	70
	185/65R14	WINTER		86 Q/T	5.5	530	300	596	189	C	C	2	70
	165/70R14	WINTER		81 Q/T	5.0	462	300	588	170	C	C	2	70
	175/70R14	WINTER		84 Q/T	5.0	500	300	602	177	C	C	2	70
15	195/65R15	WINTER		85 Q/T	6.0	515	300	595	201	C	C	2	71
	185/60R15	WINTER		84 Q/T	5.5	500	300	603	189	C	C	2	71
	195/60R15	WINTER		88 Q/T	6.0	560	300	615	201	C	C	2	71
	185/65R15	WINTER		88 Q/T	5.5	560	300	621	189	C	C	2	71
	195/65R15	WINTER	XL	91 Q/T	6.0	615	300	635	201	C	C	2	71
	205/65R15	WINTER		94 Q/T	6.0	670	300	647	209	C	C	2	71
16	205/55R16	WINTER		91 Q/T	6.5	615	300	632	214	C	C	2	72
	225/55R16	WINTER	XL	95 Q/T	7.0	690	300	654	233	C	C	2	72
	205/60R16	WINTER	XL	92 Q/T	6.0	630	300	652	209	C	C	2	72
	215/60R16	WINTER	XL	95 Q/T	6.5	690	340	664	221	C	C	2	72
	215/65R16	WINTER		98 Q/T	6.5	750	300	686	221	C	C	2	72
	215/70R16	WINTER		100 Q/T	6.5	800	300	708	221	C	C	2	72
17	225/70R16	WINTER	XL	103 Q/T	6.5	875	300	722	228	C	C	2	72
	225/50R17	WINTER	XL	94 Q/H	7.0	670	300	658	233	C	C	2	72
	215/55R17	WINTER		94 Q/H	7.0	670	300	668	226	C	C	2	72
	225/55R17	WINTER	XL	97 Q/H	7.0	730	300	680	233	C	C	2	72
	235/55R17	WINTER	XL	99 Q/H	7.5	775	300	690	245	C	C	2	72
	215/60R17	WINTER		96 Q/T	6.5	710	300	690	221	C	C	2	72
18	225/60R17	WINTER		99 Q/T	6.5	775	300	702	228	C	C	2	72
	225/65R17	WINTER		102 Q/T	6.5	850	300	724	228	C	C	2	72
	235/65R17	WINTER	XL	104 Q/T	7.0	900	300	738	240	C	C	2	72
	235/60R18	WINTER	XL	103 Q/T	7.0	875	340	739	240	C	C	2	72
	185R14C	WINTER		102/100 Q/S	5.5	850/800	450	650	188	C	C	2	70
	195/70R15C	WINTER		104/102 Q/S	6.0	900/850	450	655	201	C	C	2	70
LTR	LT215/70R15	WINTER		98/95 Q/T	6.5	750/690	350	683	221	C	C	2	71
	LT215/75R15	WINTER		100/97 Q/T	6.0	800/730	350	703	216	C	C	2	71
	LT235/75R15	WINTER		104/101 Q/T	6.5	900/825	350	733	235	C	C	2	71

# MIX-PIC BR



INCH	SIZE	TYPE	LOAD INDEX / SPEED SYMBOL	STANDARD RIM	MAX. LOAD	MAX. PRESSURE	TIRE DIMENSION		EU LABEL DATA			
				INCH	KG	KPA	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)				
13	165/70R13C	LIGHT TRUCK&VAN	88/86	5.0	560/530	375	562	170	C	C	2	70
	185R14C	LIGHT TRUCK&VAN	102/100	5.5	850/800	450	650	188	C	C	2	70
14	195R14C	LIGHT TRUCK&VAN	106/104	5.5	950/900	450	666	198	C	C	2	70
	195/70R15C	LIGHT TRUCK&VAN	104/102	6.0	900/850	450	655	201	C	C	2	71
15	215/70R15C	LIGHT TRUCK&VAN	109/107	6.5	1030/975	450	683	221	C	C	2	71
	225/70R15C	LIGHT TRUCK&VAN	112/110	6.5	1120/1060	450	697	228	C	C	2	71
	195R15C	LIGHT TRUCK&VAN	106/104	5.5	950/900	450	693	196	C	C	2	71
16	215/60R16C	LIGHT TRUCK&VAN	108/106	6.5	1000/950	475	664	221	C	C	2	71
	195/65R16C	LIGHT TRUCK&VAN	104/102	6.0	900/850	475	660	201	C	C	2	71
	205/65R16C	LIGHT TRUCK&VAN	107/105	6.0	975/925	475	672	209	C	C	2	71
	215/65R16C	LIGHT TRUCK&VAN	109/107	6.5	1030/975	475	686	221	C	C	2	72
	225/65R16C	LIGHT TRUCK&VAN	112/110	6.5	1120/1060	475	698	228	C	C	2	72
	235/65R16C	LIGHT TRUCK&VAN	115/113	7.0	1215/1150	475	712	240	C	C	2	72
	185/75R16C	LIGHT TRUCK&VAN	104/102	5.0	900/850	475	684	184	C	C	2	72
	195/75R16C	LIGHT TRUCK&VAN	107/105	5.5	975/925	475	698	196	C	C	2	72
	205/75R16C	LIGHT TRUCK&VAN	113/111	5.5	1150/1090	525	714	203	C	C	2	72
	215/75R16C	LIGHT TRUCK&VAN	116/114	6.0	1250/1180	525	728	216	C	C	2	72

# MIX-PIC



INCH	SIZE	TYPE	LOAD INDEX / SPEED SYMBOL	APPROVED RIM	MAX. LOAD	MAX. PRESSURE	TIRE DIMENSION		EU LABEL DATA			
				INCH	KG	KPA	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)				
14	185R14C	LIGHT TRUCK&VAN	102/100Q	5.0-5.5-6.0	850	450	650	188				
	195R14C	LIGHT TRUCK&VAN	106/104Q	5.0-5.5-6.0	925	450	666	198				
	205R14C	LIGHT TRUCK&VAN	109/107Q	5.5-6.0-6.5	975	450	686	208				
15	185R15C	LIGHT TRUCK&VAN	103/102Q	5.0-5.5-6.0	875	450	674	188				
16	185/75R16C	LIGHT TRUCK&VAN	104/102S	5.0-5.5-6.0	800	475	684	184				



# MIX-PIC TAXI

UTQG: 800/A/B



fuel saving  
safety  
wear  
handling

INCH	SIZE	TYPE	STD/X L	LOAD INDEX / SPEED SYMBOL	STANDARD RIM		MAX. PRESSU RE	TIRE DIMENSION	
					INCH	KG		KPA	OVERALL DIAMETER (MM)
13	165/70R13	SPECIAL SERVICE		79	5.0	437	300	562	170
	165/70R13	SPECIAL SERVICE	XL	83	5.0	487	340	562	170
	175/70R13	SPECIAL SERVICE		82	5.0	475	300	576	177
	185/70R13	SPECIAL SERVICE		86	5.5	530	300	590	189
14	185/60R14	SPECIAL SERVICE		82	5.5	475	300	578	189
	195/60R14	SPECIAL SERVICE		86	6.0	530	300	590	201
15	195/60R15	SPECIAL SERVICE		88	6.0	560	300	615	201
	185/65R15	SPECIAL SERVICE		88	5.5	560	300	621	189
	195/65R15	SPECIAL SERVICE		91	6.0	615	300	635	201
16	205/55R16	SPECIAL SERVICE		91	6.5	615	300	632	214

# MIX-PIC TOUR



comfort  
damage  
wear  
silence

INCH	SIZE	TYPE	LOAD INDEX / SPEED SYMBOL	STANDARD RIM		MAX. PRESSU RE	TIRE DIMENSION		EU LABEL DATA			
				INCH	KG		KPA	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)			
15	P205/70R15	SPECIAL SERVICE	96T	6.0	710	300	669	209	C	C	2	69
	P215/70R15	SPECIAL SERVICE	98T	6.5	750	300	683	221	C	C	2	69
	P225/70R15	SPECIAL SERVICE	100T	6.5	800	300	697	226	C	C	2	69
	P205/75R15	SPECIAL SERVICE	97T	5.5	730	300	689	203	C	C	2	69
	P215/75R15	SPECIAL SERVICE	100T	6.0	800	300	703	216	C	C	2	69
	P225/75R15	SPECIAL SERVICE	102T	6.0	850	300	719	223	C	C	2	69
	P235/75R15	SPECIAL SERVICE	105T	6.5	925	300	733	235	C	C	2	69
16	P205/55R16	SPECIAL SERVICE	91T	6.5	615	300	632	214	C	C	2	69

## Use and Maintenance

### STORAGE

- > Keep the tyres clean and away from heat, light, ozone or hydrocarbon sources.
- > Avoid prolonged exposure of the tyres to direct sunlight.
- > Avoid any contact with grease, petrol, volatile solvents or other substances that may deteriorate the rubber.
- > Avoid horizontal storage for tubeless tyres, only small size tyres may be stacked or stored flat (maximum 6 months).
- > When tyres are stored flat (horizontal), the position must be lug against lug.
- > Reduce inflation pressure when tyres are stored fitted on rims.
- > Ensure there is no water or moisture inside the tyre.
- > Never store tyres directly in contact with the ground for long periods.

### PROPER USE OF TYRES

- > When loading tyres you have to consider the correlation between speed, inflation pressure and load capacity.
- > Overloading results in premature tyre failure. Use the technical documentation and inflation tables which show the load and pressure figures for different operating speeds.
- > Underinflation results not only in incorrect tread wear but also in ply separation and eventually further damage to the ply.
- > Overinflation makes the tyre stiff and decreases its resistance against hits, leading to ply tear.

### REPAIRS TO TYRES

- > For safety reasons, repairs should only be carried out by specialists using the correct tools.



Check inflation pressure regularly



Avoid contact with grease, oil and other chemicals



Inspect tyres for damage and irregularities



Observe tyre and vehicle load limits



Read safety and maintenance recommendations



Use only authorised repair