Snake

...Keeps You Moving

Snake

AGRI-R1

BIAS TRACTOR REAR TYRES (R-1)

- Specially designed for better traction, self cleaning and stability.
- Ideally suitable in all operating conditions.
- Superior tread.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Static Loaded Radius		Rolling Circumference (±) 2.5%		Load Capacity		Inflation Pressure		Load Index	SPEED	
		Inch		mm	inch	mm	inch	mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
8.00-20	8	7.0	TT	229	9.0	965	38.0	457	18.0	2845	112.0	920	2024	2.1	30	105	A6/30 kmph	A6/20 mph
8.3-20	8	7.0	TT	211	8.3	900	35.4	406	16.0	2704	106.5	825	1808	2.5	35	101	A6/30 kmph	A6/20 mph
9.5-20	8	7.0	TT	241	9.5	955	37.6	432	17.0	2942	115.8	975	2145	2.8	41	107	A6/30 kmph	A6/20 mph
11.2-20	8	10.0	TT	284	11.2	998	39.7	483	19.0	2997	118.0	1090	2398	2.4	35	111	A6/30 kmph	A6/20 mph
	12											1215	2675	2.8	40	115	A6/30 kmph	A6/20 mph
8.3-22	6	7.0	TT	211	8.3	950	37.4	457	18.0	2972	117.0	800	1760	2.8	41	100	A6/30 kmph	A6/20 mph
	8	7.0	TT	241	9.5	991	39.3					900	1980	3.1	45	104	A6/30 kmph	A6/20 mph
9.5-22	6	7.0	TT	241	9.5	991	39.3	457	18.0	2972	117.0	900	1980	2.2	32	104	A6/30 kmph	A6/20 mph
	8											1060	2335	2.9	42	110	A6/30 kmph	A6/20 mph
8.3-24	6	7.0	TT	211	8.3	993	39.1	457	18.0	2921	115.0	800	1760	2.4	35	100	A6/30 kmph	A6/20 mph
	8											925	2035	3.1	45	105	A6/30 kmph	A6/20 mph
9.5-24	6	7.0	TT	241	9.5	1050	41.3	483	19.0	3099	122.0	850	1870	2.1	31	102	A8/40 kmph	A8/25 mph
	8											1120	2464	2.9	41	112	A6/30 kmph	A6/20 mph
	12											1360	2990	3.8	55	119	A6/30 kmph	A6/20 mph
11.2-24	6	10.0	TT	284	11.2	1105	43.5	508	20.0	3251	128.0	950	2090	2.4	35	106	A6/30 kmph	A6/20 mph
	8											1250	2750	2.4	35	116	A6/30 kmph	A6/20 mph
	10											1400	3080	3.0	44	120	A6/30 kmph	A6/20 mph
	12											1360	3000	2.8	41	119	A6/30 kmph	A6/20 mph
12.4-24	8	11.0	TT	315	12.4	1170	46.0	533	21.0	3404	134.0	1450	3190	2.3	33	121	A6/30 kmph	A6/20 mph
	12											1800	3960	3.5	50	128	A6/30 kmph	A6/20 mph
13.6-24	8	12.0	TT	345	13.5	1210	47.6	559	22.0	3556	140.0	1550	3410	1.9	28	123	A6/30 kmph	A6/20 mph
	12											1900	4180	2.8	41	130	A6/30 kmph	A6/20 mph
14.9-24	8	13.0	TT	378	14.9	1265	49.8	584	23.0	3708	146.0	1800	3960	1.8	26	128	A6/30 kmph	A6/20 mph
	12		TT/TL									2180	4795	2.6	37	135	A6/30 kmph	A6/20 mph
21.3-24	12	18.0	TT/TL	540	21.3	1400	55.1	644	25.3	4221	166.1	3860	8492	2.2	32	155	A8/40 kmph	A8/25 kmph
	16											4500	9900	2.8	40	160	A8/40 kmph	A8/25 kmph
13.6-26	8	12.0	TT	345	13.6	1260	49.6	584	23.0	3708	146.0	1700	3740	2.1	31	126	A6/30 kmph	A6/20 mph
14.9-26	8	13.0	TT	378	14.9	1315	51.7	610	24.0	3861	152.0	1850	4070	1.8	26	129	A6/30 kmph	A6/20 mph
	12											2240	4928	2.6	38	136	A6/30 kmph	A6/20 mph
23.1-26	12	20.0	TT/TL	587	23.1	1585	62.4	720	28.3	4806	189.2	3650	8030	1.7	25	153	A6/30 kmph	A6/20 mph
	16											4375	9625	2.3	33	159	A6/30 kmph	A6/20 mph
	18											4625	10175	2.6	38	161	A6/30 kmph	A6/20 mph
11.2-28	8	10.0	TT	284	11.2	1205	47.4	559	22.0	3531	139.0	1320	2904	2.4	34	118	A6/30 kmph	A6/20 mph
	12											1450	3190	2.5	36	121	A6/30 kmph	A6/20 mph
12.4-28	8	11.0	TT	378	14.9	1265	49.8	584	23.0	3708	146.0	1550	3410	2.3	33	123	A6/30 kmph	A6/20 mph
	12											1950	4290	3.4	50	131	A6/30 kmph	A6/20 mph
13.6-28	8	12.0	TT	378	14.9	1320	52.0	584	23.0	3861	152.0	1650	3630	2.0	29	125	A6/30 kmph	A6/20 mph
	12											2120	4664	2.9	41	134	A6/30 kmph	A6/20 mph
14.9-28	8	13.0	TT	378	14.9	1365	53.7	635	25.0	4013	158.0	1900	4180	1.8	26	130	A6/30 kmph	A6/20 mph
	10											2000	4400	2.1	31	132	A6/30 kmph	A6/20 mph
	12											2300	5070	2.6	38	137	A6/30 kmph	A6/20 mph
16.9-28	8	15.0	TT	429	16.9	1435	56.5	660	26.0	4216	166.0	2180	4796	1.8	25	135	A6/30 kmph	A6/20 mph
	12											2725	5995	2.4	35	143	A6/30 kmph	A6/20 mph
16.9-30	8	15.0	TT	429	16.9	1486	58.5	686	27.0	4369	172.0	2300	5060	1.7	24	137	A6/30 kmph	A6/20 mph
	12											2725	5995	2.4	36	139	A6/30 kmph	A6/20 mph
	14											3000	6600	2.8	41	143	A6/30 kmph	A6/20 mph
18.4-30	8	16.0	TT	467	18.4	1560	61.4	711	28.0	4547	179.0	2430	5345	1.4	20	139	A6/30 kmph	A6/20 mph
	10											2900	6380	1.8	26	145	A6/30 kmph	A6/20 mph
	14											3450	7590	2.6	38	151	A6/30 kmph	A6/20 mph

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Static Loaded Radius		Rolling Circumference (±) 2.5%		Load Capacity		Inflation Pressure		Load Index	SPEED	
		Inch		mm	inch	mm	inch	mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
12.4-32	8	11.0	TT	325	12.8	1359	53.5	635	25.0	3988	157.0	1600	3520	2.3	33	124	A6/30 kmph	A6/20 mph
	12											1900	4180	3.0	44	130	A6/30 kmph	A6/20 mph
16.9-34	8	15.0	TT	430	16.9	1590	62.6	737	29.0	4648	183.0	2430	5346	1.7	25	139	A6/30 kmph	A6/20 mph
	14											3000	6600	2.8	41	146	A6/30 kmph	A6/20 mph
18.4-34	8	16.0	TT	467	18.4	1660	65.3	762	30.0	4851	191.0	2650	5830	1.4	20	142	A6/30 kmph	A6/20 mph
	10											2800	6160	1.8	26	144	A6/30 kmph	A6/20 mph
	12											3000	6600	2.2	32	146	A6/30 kmph	A6/20 mph
	14											3750	8250	2.4	35	154	A6/30 kmph	A6/20 mph
20.8-34	14	18.0	TT	528	20.8	1760	69.2	790	31.1	5156	203.0	3250	7150	1.4	20	149	A6/30 kmph	A6/20 mph
	18											3650	8030	1.8	26	153	A6/30 kmph	A6/20 mph
12.4-36	8	11.0	TT	325	13.0	1465	58.0	696	28.0	4546	186.0	1700	3740	2.3	33	126	A6/30 kmph	A6/20 mph
	12											2120	4664	2.8	41	134	A6/30 kmph	A6/20 mph
13.6-36	8	12.0	TT	345	13.6	1520	59.5	717	28.2	4647	183.0	1850	4070	2.0	29	129	A6/30 kmph	A6/20 mph
	10											2060	4530	2.2	32	133	A6/30 kmph	A6/20 mph
	12											2300	5060	2.5	36	137	A6/30 kmph	A6/20 mph
12.4-38	8	11.0	TT	315	12.4	1511	59.5	716	28.2	4496	177.0	1750	3850	2.3	33	127	A6/30 kmph	A6/20 mph
	12											2120	4664	2.8	40	134	A6/30 kmph	A6/20 mph
13.6-38	6	12.0	TT	345	13.6	1565	61.6	737	29.0	4597	181.0	1700	3740	1.6	23	126	A6/30 kmph	A6/20 mph
	8											1950	4290	2.0	28	131	A6/30 kmph	A6/20 mph
	12											2430	5360	3.0	44	139	A6/30 kmph	A6/20 mph
	14											2650	5830	3.5	51	142	A6/30 kmph	A6/20 mph
14.00-38	8	12.0	TT	355	14.0	1570	61.8	737	29.0	4597	181.0	1950	4290	2.0	28	131	A6/30 kmph	A6/20 mph
	12											2430	5346	3.0	44	139	A6/30 kmph	A6/20 mph
14.9-38	8	13.0	TT	378	15.0	1685	66.3	737	29.0	4597	181.0	2120	4664	2.4	35	134	A6/30 kmph	A6/20 mph
	12											2575	5665	3.0	43	141	A6/30 kmph	A6/20 mph
15.5-38	8	14.0	TT	395	15.5	1585	62.4	737	29.0	4648	183.0	2060	4532	1.8	26	133	A6/30 kmph	A6/20 mph
	12											2575	5665	2.8	41	141	A6/30 kmph	A6/20 mph
16.9-38	8	15.0	TT	429	16.9	1685	66.3	787	31.0	4953	195.0	2575	5665	1.8	26	141	A6/30 kmph	A6/20 mph
	14											3450	7590	2.4	35	151	A6/30 kmph	A6/20 mph
18.4-38	8	16.0	TT	467	18.4	1770	69.6	813	32.0	5156	203.0	2725	5995	1.4	20	143	A6/30 kmph	A6/20 mph
	12											3450	7590	2.1	30	151	A6/30 kmph	A6/20 mph
	14											3650	8030	2.3	33	153	A6/30 kmph	A6/20 mph
20.8-38	8	18.0	TT	528	20.8	1840	72.4	864	34.0	5385	212.0	3150	6930	1.3	19	148	A6/30 kmph	A6/20 mph
	10											3350	7370	1.5	22	150	A6/30 kmph	A6/20 mph
	12											4000	8800	2.0	29	156	A6/30 kmph	A6/20 mph
	14											4500	9900	2.4	35	160	A6/30 kmph	A6/20 mph
	28											5800	12760	4.3	62	169	A6/30 kmph	A6/20 mph

AGRI-1 +

BIAS TRACTOR REAR TYRES (R-1)

- Unique lug design ensures excellent traction in both dry and wet soil conditions.
- Specially designed profile for better stability.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Static Loaded Radius		Rolling Circumference (±) 2.5%		Load Capacity		Inflation Pressure		Load Index	SPEED	
		Inch		mm	inch	mm	inch	mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
16.9-26	12	14.0	TT/TL	429	16.9	1385	54.5	635	25.0	4064	160.0	2300	5060	2.3	33	137	A8/40 kmph	A8/25 kmph
												2500	5500	2.3	33	140	A6/30 kmph	A6/20 mph

Snake

F-2

BIAS TRACTOR FRONT TYRES

- Penetrates deep into soil for maximum steering control and minimal lateral side-slip because of its high center rib.
- Best for handling heavy loads on hard-packed surfaces.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Static Loaded Radius		Rolling Circumference (±) 2.5%		Load Capacity		Inflation Pressure		Load Index	SPEED	
		Inch		mm	inch	mm	inch	mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
3.50-6	4	2.5	TT	99	3.9	343	13.5	214	8.4	1341	52.8	165	363	2.7	38	45	A8/40 kmph	A8/25 mph
3.50-8	4	2.5	TT	101	4.0	371	14.6	218	8.6	1390	54.7	185	407	2.7	38	49	A8/40 kmph	A8/25 mph
4.00-8	4	3.0	TT	112	4.4	430	16.9	224	8.8	1430	56.3	224	493	2.8	40	56	A8/40 kmph	A8/25 mph
4.00-12	4	3.0	TT	112	4.4	530	20.8	254	10.0	1626	64.0	300	660	2.8	40	66	A8/40 kmph	A8/25 mph
4.00-15	4	3.0	TT	112	4.4	610	24.0	295	11.6	1854	73.0	307	675	2.8	40	67	A8/40 kmph	A8/25 mph
5.00-15	6	4.0	TT	140	5.5	655	25.8	305	12.0	1956	77.0	475	1045	3.7	54	82	A8/40 kmph	A8/25 mph
4.00-16	4	3.0	TT	112	4.4	640	25.2	305	12.0	1956	77.0	325	715	3.3	48	69	A6/30 kmph	A6/20 mph
4.50-16	6	3.0	TT	122	4.8	665	26.2	305	12.0	1956	77.0	365	803	3.2	47	73	A6/30 kmph	A6/20 mph
5.00-16	6	4.0	TT	140	5.5	680	26.8	330	13.0	2032	80.0	400	880	3.3	48	76	A8/40 kmph	A8/25 mph
5.50-16	6	4.0	TT	150	5.9	710	27.9	330	13.0	2083	82.0	425	935	3.3	48	78	A8/40 kmph	A8/25 mph
6.00-16	8	4.5	TT	165	6.5	745	29.3	356	14.0	2184	86.0	670	1474	4.4	64	94	A6/30 kmph	A6/20 mph
6.50-16	8	4.5	TT	175	6.8	760	29.9	356	14.0	2286	90.0	750	1650	3.3	48	98	A6/30 kmph	A6/20 mph
7.50-16	8	5.5	TT/TL	205	8.0	808	31.8	381	15.0	2413	95.0	875	1925	3.7	54	103	A6/30 kmph	A6/20 mph
	12	5.5	TT									1150	2530	4.7	68	113	A8/40 kmph	A8/25 mph
9.00-16	10	7.0	TT/TL	234	9.2	854	33.6	406	16.0	2540	100.0	1250	2750	3.8	55	116	A6/30 kmph	A6/20 mph
10.00-16	10	7.0	TT/TL	275	10.8	900	35.4	406	16.0	2692	106.0	1360	2992	2.8	41	119	A8/40 kmph	A8/25 mph
11.00-16	12	10	TT/TL	320	12.6	970	38.1	457	18.0	2896	114.0	1600	3520	2.5	36	124	A8/40 kmph	A8/25 mph
7.50-18	8	5.5	TT	204	8.0	867	34.2	406	16.0	2565	101.0	950	2090	3.7	54	106	A8/40 kmph	A8/25 mph
	12											1350	2970	3.9	57	119	A8/40 kmph	A8/25 mph
4.00-19	6	3.0	TT	112	4.4	712	28.0	330	13.0	2134	84.0	355	781	3.4	48	72	A6/30 kmph	A6/20 mph
6.00-19	8	4.5	TT	165	6.5	814	32.0	381	15.0	2413	95.0	615	1353	3.3	48	91	A8/40 kmph	A8/25 mph
6.50-20	8	4.5	TT	173	6.8	864	34.0	406	16.0	2565	101.0	850	1870	3.3	48	102	A6/30 kmph	A6/20 mph
7.50-20	8	5.5	TT	203	8.0	920	36.2	432	17.0	2718	107.0	1030	2266	3.5	50	109	A6/30 kmph	A6/20 mph
	12											1320	2904	4.0	58	118	A6/30 kmph	A6/20 mph

Snake

SKS-1

SKID STEER TYRES

- Premium conventional skid steer tyre with deeper tread depth, premium compound, large tread lugs heavier sidewall.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Static Loaded Radius		Rolling Circumference (±) 2.5%		Load Capacity		Inflation Pressure		Load Index	SPEED	
		Inch		mm	inch	mm	inch	mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
10-16.5	10	8.25	TL	268	10.5	795	31.3	356	14.0	2286	90.0	1550	3410	5.1	74	123	A8/40 kmph	A8/25 mph
	12											1700	3740	5.2	75	126	A8/40 kmph	A8/25 mph
12-16.5	12	9.75	TL	325	12.8	853	33.6	381	15.0	2438	96.0	2060	4532	5.4	78	133	A8/40 kmph	A8/25 mph
	14											2300	5060	6.2	90	137	A8/40 kmph	A8/25 mph

Snake

IND R-4

INDUSTRIAL BACKHOE LOADER TYRES

- Extra wide lugs designed to resist buckling, tearing and cracking.
- Excellent tread wear and road ability, the laterally designed lugs result in even wear.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Static Loaded Radius		Rolling Circumference (±) 2.5%		Load Capacity		Inflation Pressure		Load Index	SPEED	
		Inch		mm	inch	mm	inch	mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
33x12.5-15	8	10.0	TL	318	12.5	851	33.5	381	15.0	2489	98.0	2120	4664	3.2	46	134	A8/40 kmph	A8/25 mph
12.5/70-16	14	10.0	TL	315	12.4	853	33.6	381	15.0	2590	102.0	1650	3630	2.6	38	125	A8/40 kmph	A8/25 mph
15.5/60-18	14	13.0	TL	401	15.8	950	37.4	432	17.0	2870	113.0	2430	5346	2.6	38	139	A8/40 kmph	A8/25 mph
15.5/70-18 (400/70-18)	12	13.0	TL	401	15.8	1031	40.6	483	19.0	3099	122.0	2430	5346	2.4	35	139	A8/40 kmph	A8/25 mph
17.5/65-20	14	14.0	TL	450	17.7	1090	42.9	483	19.0	3302	130.0	3250	7150	2.4	35	149	A8/40 kmph	A8/25 mph
16.9-24	12	15.0	TL	450	17.7	1303	51.3	584	23.0	3785	149.0	3250	7150	2.6	37	149	A8/40 kmph	A8/25 mph
	16											3875	8525	3.3	48	155	A8/40 kmph	A8/25 mph
17.5L-24	12	15.0	TL	452	17.8	1270	50.0	559	22.0	3683	145.0	3150	6930	2.6	38	148	A8/40 kmph	A8/25 mph
	16											3750	8250	3.3	48	154	A8/40 kmph	A8/25 mph
18.4-24	12	16.0	TL	472	18.6	1372	54.0	603	24.0	4039	159.0	3875	8525	2.4	35	155	A8/40 kmph	A8/25 mph
	16											4375	9625	3.0	44	159	A8/40 kmph	A8/25 mph
19.5L-24	12	16.0	TL	495	19.5	1321	52.0	584	23.0	3835	151.0	3450	7590	2.3	33	151	A8/40 kmph	A8/25 mph
	16											4125	9075	3.0	44	157	A8/40 kmph	A8/25 mph
18.4-26	12	16.0	TL	480	18.9	1422	56.0	635	25.0	4140	163.0	4000	8800	2.4	36	156	A8/40 kmph	A8/25 mph
	16											4875	10725	3.1	45	163	A8/40 kmph	A8/25 mph
16.9-28	12	15.0	TL	450	17.7	1410	55.5	635	25.0	4140	163.0	3550	7810	2.6	38	152	A8/40 kmph	A8/25 mph
	16											4125	9075	3.3	48	157	A8/40 kmph	A8/25 mph

F-3

INDUSTRIAL BACKHOE LOADER TYRES

- Specially designed for soil tillage operations.
- Suitable for implement machinery and trailers.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Static Loaded Radius		Rolling Circumference (±) 2.5%		Load Capacity		Inflation Pressure		Load Index	SPEED	
		Inch		mm	inch	mm	inch	mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
11L-15	12	8.0	TL	280	11.0	813	32.0	355	14.0	2362	93.0	1180	2596	4.0	58	114	A8/40 kmph	A8/25 mph
11L-16	12	8.0	TL	280	11.0	820	32.3	381	15.0	2438	96.0	1250	2750	4.3	62	116	A8/40 kmph	A8/25 mph
	14											1360	2992	4.8	70	119	A8/40 kmph	A8/25 mph

Snake

COBRA

INDUSTRIAL BACKHOE LOADER TYRES

- Extra deep tread with sturdy lug design. Strong casing with heat and cut resistant tread compound provide longer life. Extra thick side wall with rim guard gives protection against damage.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Static Loaded Radius		Rolling Circumference (±) 2.5%		Load Capacity		Inflation Pressure		Load Index	SPEED	
		Inch		mm	inch	mm	inch	mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
11L-16	14	8.0	TL	280	11.0	820	32.3	381	15.0	2438	96.0	1360	2992	4.8	70	119	A8/40 kmph	A8/25 mph
12.5/80-18	12	9.0	TL	305	12.0	975	38.4	432	17.0	2896	114.0	2120	4665	3.1	45	134	A8/40 kmph	A8/25 mph
	16											2650	5830	3.8	55	142	A8/40 kmph	A8/25 mph
19.5L-24	16	17.0	TL	490	19.3	1298	51.1	589	23.2	3835	151.0	4125	9075	3.0	44	157	A8/40 kmph	A8/25 mph
18.4-26	16	16.0	TL	475	18.7	1425	56.1	635	25.0	4191	165.0	4875	10725	3.1	45	163	A8/40 kmph	A8/25 mph
16.9-28	16	15.0	TL	440	17.3	1410	55.5	635	25.0	4140	163.0	4250	9350	3.5	50	158	A8/40 kmph	A8/25 mph

IND R-4

INDUSTRIAL BACKHOE LOADER TYRES

- Strong and sturdy heavy duty design.
- Effective self cleaning properties.
- Ideal for backhoe loaders.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Static Loaded Radius		Rolling Circumference (±) 2.5%		Load Capacity		Inflation Pressure		Load Index	SPEED	
		Inch		mm	inch	mm	inch	mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
16.9-24	12	15.0	TL	440	17.3	1308	51.5	584	23.0	3861	152.0	3250	7150	2.6	38	149	A8/40 kmph	A8/25 mph
	16											3875	8525	3.3	48	155	A8/40 kmph	A8/25 mph
17.5L-24	12	15.0	TL	445	17.5	1270	50.0	559	22.0	3683	145.0	3150	6930	2.6	38	148	A8/40 kmph	A8/25 mph
	16											3750	8250	3.3	48	154	A8/40 kmph	A8/25 mph
18.4-24	12	16.0	TL	472	18.6	1375	54.1	603	32.7	4039	159.0	3875	8525	2.4	35	155	A8/40 kmph	A8/25 mph
	16											4375	9625	3.0	44	159	A8/40 kmph	A8/25 mph
19.5L-24	12	16.0	TL	495	19.5	1325	52.1	584	23.0	3835	151.0	3450	7590	2.3	33	151	A8/40 kmph	A8/25 mph
	16											4125	9075	3.0	44	157	A8/40 kmph	A8/25 mph
21L-24	12	18.0	TL	533	21.0	1377	54.2	610	24.0	3988	157.0	3875	8525	2.2	32	155	A8/40 kmph	A8/25 mph
	16											4500	9900	2.6	38	160	A8/40 kmph	A8/25 mph
18.4-26	12	16.0	TL	475	18.7	1425	56.1	635	25.0	4191	165.0	4000	8800	2.4	35	156	A8/40 kmph	A8/25 mph
	16											4875	10725	3.1	45	163	A8/40 kmph	A8/25 mph
16.9-28	12	15.0	TL	440	17.3	1410	55.5	635	25.0	4140	163.0	3550	7810	2.6	38	152	A8/40 kmph	A8/25 mph
	16											4125	9075	3.3	48	157	A8/40 kmph	A8/25 mph
16.9-30	12	15.0	TL	440	17.3	1460	57.5	660	26.0	4216	166.0	3650	8030	2.6	38	153	A8/40 kmph	A8/25 mph
	16											4250	9350	3.1	45	158	A8/40 kmph	A8/25 mph

Snake

MPT-1

INDUSTRIAL BACKHOE LOADER TYRES

- Extra wide lugs designed to resist buckling, tearing and cracking.
- Multi step lug design provides better self cleaning and stability.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Static Loaded Radius		Rolling Circumference (±) 2.5%		Load Capacity		Inflation Pressure		Load Index	SPEED	
		Inch		mm	inch	mm	inch	mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
10.5/80-18	10	9.0	TL	267	10.8	910	35.8	406	16.0	2667	105.0	1950	4290	5.0	72	131	A8/40 kmph	A8/25 mph
12.5/80-18	12	9.0	TL	307	12.1	988	38.9	432	17.0	2896	114.0	2650	5830	3.7	54	142	A8/40 kmph	A8/25 mph
	16											3150	6930	4.9	70	148	A8/40 kmph	A8/25 mph