SOLIDANA

ECO

MATERIAL HANDLING TIRES

THE PERFORMER

Optimized for Value

THE PERFORMER is simple and efficient, providing perfect performance at a competitive price.

ENERGY SAVING
Good energy saving and efficiency due to low rolling resistance.

OPERATING TIME
Good operating time in suitable applications.

LIFE TIME
Good tire life providing very good value.

CORNERING STABILITY
Good cornering stability enabling safety and comfort.

Low abrasion tread compound.

High lug depth and optimized aspect ratio.



GRI
WE'LL GET YOU THERE

Tire Size	Rim Size	Clip on	Profile	Tire Dimensions		Tire Dimensions		Tire load capacity on forklifts at Max. Speed			
								12 Miles/h (Lbs)		20 Km/h (Kg)	
				Max width ±1% (mm)	OD ± 2% (mm)	Max width ±1% (inch)	OD ± 2% (Inch)	Load wheel	Steer wheel	Load wheel	Steer wheel
4.00-8	3.00 D-8		GS	104	406	4.09	15.98	2095	1610	950	730
5.00-8	3.00 D-8		GS	116	446	4.57	17.56	3120	2405	1415	1090
15x4 1/2-8 125/75-8	3.00 D-8	•	GS	103	377	4.06	14.84	2295	1765	1040	800
16x6-8 150/75-8	4.33 R-8	•	GS	139	407	5.47	16.02	3210	2535	1455	1150
18x7-8 180/70-8	4.33 R-8	•	GS	153	451	6.02	17.76	4730	3640	2145	1650
6.00-9	4.00 E-9	•	GS	139	520	5.51	20.47	4155	3195	1885	1450
21x8-9 200/75-9	6.00 E-9	•	GS	174	516	6.85	20.31	6075	4675	2755	2120
6.50-10	5.00 F-10	•	GS	153	565	6.02	22.24	5160	3970	2340	1800
200/50-10	6.50 F-10	•	GS	188	456	7.40	17.95	5445	4190	2470	1900
23x9-10 225/75-10	6.50 F-10	•	GS	188	582	7.52	22.80	7595	5840	3445	2650
7.00-12	5.00 S-12	•	GS	164	647	6.46	25.47	6435	4940	2920	2240
23x10-12	8.00 G-12	•	GS	234	580	9.21	22.83	8310	6390	3770	2900
27x10-12 250/75-12	8.00 G-12	•	GS	232	675	9.13	26.50	8600	6615	3900	3000
7.00-15	5.50-15	•	GS	175	705	7.01	27.76	7815	6005	3545	2725
7.00-15	6.00-15	•	GS	175	705	7.01	27.76	7815	6005	3545	2725
250-15 250/70-15	7.00-15	•	GS	211	712	8.43	28.03	10470	8045	4750	3650
250-15 250/70-15	7.50-15	•	GS	211	712	8.43	28.03	10470	8045	4750	3650
8.15-15 (28x9-15) 225/75-15	7.00-15	•	GS	202	681	8.23	26.81	8310	6390	3770	2900
8.25-15	5.50-15	•	GS	194	809	7.64	31.85	10470	8045	4750	3650
8.25-15	6.50-15	•	GS	193	809	7.60	31.85	10470	8045	4750	3650
300-15 315/70-15	8.00-15	•	GS	243	812	9.57	31.97	12895	9920	5850	4500
355/65-15	9.75-15	•	GS	291	826	11.46	32.52	17190	13230	7800	6000
9.00-20	6.50-10		GS	225	971	8.86	38.23	11770	9810	5340	4450
9.00-20	7.00-20		GS	225	971	8.86	38.23	11770	9810	5340	4450
10.00-20	7.00-20		GS	250	1006	9.84	39.61	13230	11025	6000	5000
10.00-20	7.50-20		GS	250	1006	9.84	39.61	13230	11025	6000	5000
10.00-20	8.00-20		GS	250	1006	9.84	39.61	13230	11025	6000	5000
11.00-20	7.50-20		GS	265	1088	10.43	42.83	14420	12015	6540	5450
11.00-20	8.00-20		GS	265	1088	10.43	42.83	14420	12015	6540	5450
11.00-20	8.50-20		GS	265	1088	10.43	42.83	14420	12015	6540	5450
12.00-20	8.00-20		GS	265	1088	10.43	42.83	16535	13780	7500	6250
12.00-20	8.50-20		GS	265	1088	10.43	42.83	16535	13780	7500	6250

PERFORMANCE

ENERGY SAVINGS

COMFORT

TIRE LIFE

SOLIDANA ECO

MATERIAL HANDLING TIRES

SUITABLE FOR LIFTER OR FORKLIFT
IN TOUGH WORKING CONDITIONS.
SUPER STRONG PNEUMATIC SHAPED
SOLID TIRE WITH SPECIAL COMPOUNDS.

Widen tread makes good stability and ground grasping capability.

Reasonable groove wide ratio reduce rolling resistance, make energy saving!



Designed for easy tire installationwith Excellent Rim fit.

ECO proves itself as one of the most cost-effective tires in its class. It is a two-stage tire that has good tensile strength and provides a firm but smooth ride. Our creel bead technology ensures secure and safe fitment to all forklift wheels and rims. ECO is excellent for light and intermittent use in all material handling applications.

Features & Benefits

Square footprint and increased lug depth.
Optimized aspect ratio, even wear and increased stability.
Low rolling resistance, high abrasion resistance tread.
Good mileage, optimized performance at lower cost.
Moderate driving comfort due to optimum suspension & absorption.
Low energy consumption and reduced co2 emissions.

Tire Size		Rim Size	Clip on	Profile	Tire dimensions		Tire dimensions		Tire load capacity on forklifts at Max. Speed			
									12 Miles/h (Lbs)		20 Km/h (Kg)	
					Max width ±1% (mm)	OD ± 2% (mm)	Max width ±1% (inch)	OD ± 2% (Inch)	Load wheel	Steer wheel	Load wheel	Steer wheel
4.00-8		3.00 D-8	•	GS	104	406	4.09	15.98	2095	1610	950	730
5.00-8		3.00 D-8	•	GS	116	446	4.57	17.56	3120	2405	1415	1090
15x4 1/2-8	125/75-8	3.00 D-8	•	GS	103	377	4.06	14.84	2295	1765	1040	800
16x6-8	150/75-8	4.33 R-8	•	GS	139	407	5.47	16.02	3210	2535	1455	1150
18x7-8	180/70-8	4.33 R-8	•	GS	153	451	6.02	17.76	4730	3640	2145	1650
6.00-9		4.00 E-9	•	GS	139	520	5.51	20.47	4155	3195	1885	1450
21x8-9	200/75-9	6.00 E-9	•	GS	174	516	6.85	20.31	6075	4675	2755	2120
6.50-10		5.00 F-10	•	GS	153	565	6.02	22.24	5160	3970	2340	1800
200/50-10		6.50 F-10	•	GS	188	456	7.40	17.95	5445	4190	2470	1900
23x9-10	225/75-10	6.50 F-10	•	GS	188	582	7.52	22.80	7595	5840	3445	2650
7.00-12		5.00 S-12	•	GS	164	647	6.46	25.47	6435	4940	2920	2240
23x10-12		8.00 G-12	•	GS	234	580	9.21	22.83	8310	6390	3770	2900
27x10-12	250/75-12	8.00 G-12	•	GS	232	675	9.13	26.50	8600	6615	3900	3000
7.00-15		5.50-15	•	GS	175	705	7.01	27.76	7815	6005	3545	2725
7.00-15		6.00-15	•	GS	175	705	7.01	27.76	7815	6005	3545	2725
250-15	250/70-15	7.00-15	•	GS	211	712	8.43	28.03	10470	8045	4750	3650
250-15	250/70-15	7.50-15	•	GS	211	712	8.43	28.03	10470	8045	4750	3650
8.15-15 (28x9-15)	225/75-15	7.00-15	•	GS	202	681	8.23	26.81	8310	6390	3770	2900
8.25-15		5.50-15	•	GS	194	809	7.64	31.85	10470	8045	4750	3650
8.25-15		6.50-15	•	GS	193	809	7.60	31.85	10470	8045	4750	3650
300-15	315/70-15	8.00-15	•	GS	243	812	9.57	31.97	12895	9920	5850	4500
355/65-15		9.75-15	•	GS	291	826	11.46	32.52	17190	13230	7800	6000
9.00-20		6.50-10		GS	225	971	8.86	38.23	11770	9810	5340	4450
9.00-20		7.00-20		GS	225	971	8.86	38.23	11770	9810	5340	4450
10.00-20		7.00-20		GS	250	1006	9.84	39.61	13230	11025	6000	5000
10.00-20		7.50-20		GS	250	1006	9.84	39.61	13230	11025	6000	5000
10.00-20		8.00-20		GS	250	1006	9.84	39.61	13230	11025	6000	5000
11.00-20		7.50-20		GS	265	1088	10.43	42.83	14420	12015	6540	5450
11.00-20		8.00-20		GS	265	1088	10.43	42.83	14420	12015	6540	5450
11.00-20		8.50-20		GS	265	1088	10.43	42.83	14420	12015	6540	5450
12.00-20		8.00-20		GS	265	1088	10.43	42.83	16535	13780	7500	6250
12.00-20		8.50-20		GS	265	1088	10.43	42.83	16535	13780	7500	6250